

x3POS

Unique POS, very slim and sleek can operate on the wall with VESA mount, as a kiosk, as a POS and as a tablet. Very stylish and easily adjustable to support many functional positions. Very easily also connects to peripheral devices with USB ports. The ultra thin bezel provides seamless viewing experience. Ideal for Restaurants, Convenience Stores, Hospitality, Supermarket, Retail.



VESA Mount Capable



Compact 11.6"
Space-saving



IP54 Whole Unit

SE NOR



SPECIFICATIONS

	x3S N95	x3S T312
PROCESSOR	Intel N95 1.7 GHz (Turbo Speed up to 3.4 GHz)	Intel i3 7020U 1.2 GHz (Turbo Boost up to 4.4 GHz)
SYSTEM MEMORY	8 GB DDR4 RAM	8 GB DDR4 RAM
STORAGE DEVICE	1 x 128 GB removable M.2 PCIe 2280 SSD / 1 x 128 GB removable M.2 SATA 2280 SSD	1 x 128 GB removable M.2 SATA 2280 SSD

DISPLAY

SIZE / RESOLUTION	15.6" TFT LCD (LED backlight) / Full HD 1920 x 1080 pixels
BRIGHTNESS	300 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)

I/O INTERFACE

USB PORT	5 x USB 2.0, 1 x USB 3.0 (side)
SERIAL PORT	2 x RJ50
AUDIO PORT	2 x 2 W speakers
CASH DRAWER	1 x RJ12 (24 V)
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps



OPERATING SYSTEM

WINDOWS	10 IoT (64-bit) / 10 Pro (64-bit) / 11 IoT (64-bit) / 11 Pro (64-bit)
LINUX	Kernel 3.0 up

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	285 (W) x 44~376 (H) x 195 (D) mm 4.5 kg
CHASSIS MATERIAL	Aluminium die-cast & Polycarbonate-ABS
IP RATING	IP54 whole unit
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C
HUMIDITY	10% to 90% (non-condensing)
POWER CONSUMPTION	19 V / 3.15 A, external power adaptor, 100-240 V, 50/60 Hz 19 V / 6.31 A, external power adaptor, 100-240 V, 50/60 Hz (printer integrated)

MODEL OPTIONS

INTEGRATED READERS	3-track MSR, Fingerprint reader, RFID, 2D barcode reader
CUSTOMER DISPLAY	11.6" (1980 x 1080) LCD or 2-line VFD
WIRELESS LAN	Integrated Dual Band Wi-Fi 802.11 b/g/n/ac (2x2 MIMO) + Bluetooth 4.1
COLOURS	Dark Grey (standard) White (optional)

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.